

Description:	Glueless Locking Cork Floating Floor
Warranty:	Lifetime Limited Residential Wear Warranty Lifetime Structure Warranty 5 Year Limited Light/Medium Commercial Wear Warranty
Species:	Cork
Installation:	Float
Size/Packaging:	5-1/2" x 48 1/32" x 13/32" (14.7 sq. ft/carton, 27 lbs.)
Component Thickness:	Top cork layer – 3 mm HDF layer – 6 mm Bottom cork layer – 1.5 mm
Finish:	Endura AR[®] UV-cured finish with advanced abrasion resistance
Flammability:	Passes "Life Safety Codes"
Smoke Density: [ASTM E 662-05]	Flaming: 199 / Non-Flaming: 177
Critical Radiant Flux: [ASTM E648-06]	.23 watts/cm²
IIC Impact Insulation: [ASTM E492-04]	58
STC Sound Transmission: [ASTM E413-87]	54
Moisture Content:	> 6 to < 9%
Certifications:	GREENGUARD Gold Certified for Indoor Air Quality CARB Compliant Lacey Act Compliant
Environmental Statement:	USFloors' commitment is to provide consumers and specifiers with beautiful and durable floors at a good value, while minimizing our impact on the environment and enhancing and improving it whenever possible. USFloors is a member of the USGBC.
Country of Origin:	Manufactured in Portugal.